

सं. P-47011/208/2019-टीएसडब्लू

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग संवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

131
2/83

विषय:- मैसर्स Vizag Carbon Pvt. Ltd. का आवेदन इनपुट आउटपुट मानदंडों के संबंध में।

अग्रिम प्राधिकार सं. 5010002447 दिनांक 25.05.2018

संदर्भ: 01/83/050/01288/AM19/ Dated: 27.02.2019

In this case the firm has indicated net content of raw material Electrically Calcined anthracite coal (ECA coal) as 302.8 MT in the export product and claimed wastage of 6% without giving any justification. We may allow wastage of 2% and accordingly following norms are recommended:-

Export item:-

S.No.	Item name	Quantity
1.	Electrode paste (Net content of Electrically Calcined Anthracite Coal ECA Coal 302.80 MT)	400 MT

Import item:-

S. No	Item name	Quantity
1.	Electrically Calcined anthracite coal (ECA coal)	308.856 MT


(Nand Lal)
Consultant
2019

DGFT (DES-IV)

Encl. file

F. No. 7/80/2019-TSW

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग संवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

135
3/83

Sub:- AA Nos. 0510407426 dated 03.08.2018 , 0510406825 dated 12.06.2018, 0510410576 dated 14.05.2019 & (0510407962 dated 03.10.2018) for the export of engineered wooden flooring- M/s. Green Lam Industries Ltd.

Ref: - i) 01/83/050/00490/AM19/DES-IV
ii) 01/83/050/00981/AM19/DES-IV
iii) 01/83/050/00114/AM20/DES-IV
iv) 01/83/050/00618/ AM19/DES-IV

In this case export produced product is "Engineered wooden flooring " (15.00 m) and import items are

S. No.	Import item	Wastage claimed
1.	Wood Veneer (for Top Layer)	66.67%
2.	Pine wood (for Middle Layer)	100%
3.	Wood Veneer (for Bottom layer)	53.85%
4.-8.	Glue, modifier, hardener and lacquer/paint/varnish	20%

The firm was called for personal hearing by DGFT and the firm's representatives explained the manufacturing process and wastage occurring in manufacturing the export product, giving calculation for requirement of raw materials. It has been stated that the wooden flooring has plank lock which is used to join wooden flooring with each other on the floor. There are three layers of wooden flooring and import items are 1 to 3 as stated above. The wastage is due to following reason:

- Grading Wastage because this is a natural material having some kind of holes, knots, sap wood, water mark, cracks, because of these the material becomes unusable.
- The Raw Material comes in different sizes and grades. However, the finished product requires fixed sizes and premium grade only.
- The material is required to store at a certain degree of moisture therefore, the material is stored in seasoning chamber, and thus the shrinkage wastage is also very higher.

d. Cutting wastage is also there.

After deliberation, Committee decided to fix the following norms, on one time basis in all the four A.As. as under:

Export Items: Engineered Wooden Flooring (thickness: 15.00MM)
Quantity: 1 Sq Meter

Import Items;

S.No	Item Description	Quantity recommended
1.	Wood Veneer (for top layer) (thickness:3.00MM+/- 10%)	1.5670 SQM.
2.	Pine Wood (for middle layer)	0.0188 CBM
3.	Wood Veneer (for bottom layer) (Thickness: 2.20 MM +/-10%)	0.00318 CBM
4.	Glue-urea formaldehyde	0.2338 Kg
5.	Modifier	0.0475 Kg
6.	Hardner	0.0400 Kg
7.	Lacquer/paint (UV sealer standard, UV sealer anti abrasive, UV top coat anti scratch, UV sealer matt, UV primer, UV filler, UV hydro primer white, UV sealer colourless, UV sealer lifetime, UV sealer white, UV top coat entry scratch matt, stain binder)	0.1365 Kg
8.	Lacquer/ Varnish (colour yellow, red, white, black, blue)	0.0080 Kg

DES-IV

NLP
24/7/2019
(Nand Lal)
Consultant

Government of India
Ministry of Chemicals and Fertilizers
Department of Chemicals and Petrochemicals

14/86
216
3/83

Subject: Advance Authorization application from M/s. INDOTAN Chemicals Ltd for the import of raw material against the export of BASIC CHROMIUM SULPHATE

0210208961 dt. 07/02/2019 ✓
(Advance Authorization No. 0210205670 dated 23.3.2015)

01/83/50/01185/Am-191
Ref: U.O. No. 01/83/50/380-AM-16/DES-4/571 dated 24.8.15

M/s. INDOTAN Chemicals Ltd have submitted present application for the import of raw material against the export of BASIC CHROMIUM SULPHATE

The application has been examined and the Department recommends the following norms for the present Advance Authorization application.

0210208961 dt. 07/02/2019 ✓
0210203847 dt. 05.06.14 ✓

1. Item of Export	Qty.	Item of Import	Qty
BASIC CHROMIUM SULPHATE (BASICITY 33%-35%)	1 kg	1. SODIUM DICHROMATE	0.487 kg

This issues with the approval of competent authority.


(A.K. AGARWAL)
Addl. Industrial Adviser
Tel. No. 011-2338 1430

Shri K.K.Mushahari, FTDO, (DES-IV) U/o DGFT, Udyog Bhawan, New Delhi-11.
Deptt. of C&PC U.O. No. 14010/31/2015-CH-II dated 4.12.2015

10/12

F. No. 7/80/2019-TSW

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग संवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

147
3/83

Sub:- AA Nos. **0510407426** dated 03.08.2018, **0510406825** dated 12.06.2018, **0510410576** dated 14.05.2019 & **0510407962** dated 03.10.2018 for the export of engineered wooden flooring- M/s. Green Lam Industries Ltd.

Ref: - i) 01/83/050/00490/AM19/DES-IV
ii) 01/83/050/00981/AM19/DES-IV
iii) 01/83/050/00114/AM20/DES-IV
iv) 01/83/050/00618/ AM19/DES-IV

In this case export produced product is "Engineered wooden flooring " (15.00 m) and import items are

S. No.	Import item	Wastage claimed
1.	Wood Veneer (for Top Layer)	66.67%
2.	Pine wood (for Middle Layer)	100%
3.	Wood Veneer (for Bottom layer)	53.85%
4.-8.	Glue, modifier, hardener and lacquer/paint/varnish	20%

The firm was called for personal hearing by DGFT and the firm's representatives explained the manufacturing process and wastage occurring in manufacturing the export product, giving calculation for requirement of raw materials. It has been stated that the wooden flooring has plank lock which is used to join wooden flooring with each other on the floor. There are three layers of wooden flooring and import items are 1 to 3 as stated above. The wastage is due to following reason:

- Grading Wastage because this is a natural material having some kind of holes, knots, sap wood, water mark, cracks, because of these the material becomes unusable.
- The Raw Material comes in different sizes and grades. However, the finished product requires fixed sizes and premium grade only.
- The material is required to store at a certain degree of moisture therefore, the material is stored in seasoning chamber, and thus the shrinkage wastage is also very higher.

d. Cutting wastage is also there.

After deliberation, Committee decided to fix the following norms, on one time basis in all the four A.As. as under:

Export Items: Engineered Wooden Flooring (thickness: 15.00MM)
Quantity: 1 Sq Meter

Import Items;

S.No	Item Description	Quantity recommended
1.	Wood Veneer (for top layer) (thickness:3.00MM+/- 10%)	1.5670 SQM.
2.	Pine Wood (for middle layer)	0.0188 CBM
3.	Wood Veneer (for bottom layer) (Thickness: 2.20 MM +/-10%)	0.00318 CBM
4.	Glue-urea formaldehyde	0.2338 Kg
5.	Modifier	0.0475 Kg
6.	Hardner	0.0400 Kg
7.	Lacquer/paint (UV sealer standard, UV sealer anti abrasive, UV top coat anti scratch, UV sealer matt, UV primer, UV filler, UV hydro primer white, UV sealer colourless, UV sealer lifetime, UV sealer white, UV top coat entry scratch matt, stain binder)	0.1365 Kg
8.	Lacquer/ Varnish (colour yellow, red, white, black, blue)	0.0080 Kg

DES-IV

NLP
24/7/2019
(Nand Lal)
Consultant

सं. P-47011/154/2019-टीएसडब्ल्यू

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग सर्वर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

192
3/83

विषय :-मैसर्स M/s Samrat Plywood Ltd. का आवेदन इनपुट आउटपुट मानदंडोंके संबंध में । AA No. 2210016042 dated 03.01.2019

संदर्भ:- 01/83/50/00759/AM-19 dated. 21.01.2019

Taking cue from H-68 and the cases approved in the past, the following norms are recommended:-

Export Item:

S. No.	Item Description	Quantity
1	Double Side Decorative Laminates with Barrier Paper size Thickness 1.8 mm (15106 SQM) (39010 KG)	4150 Number
2	Double Side Decorative Laminates with Barrier Paper Thickness 2.3 MM (4550 SQM) (15000KG))	1250 Number

Import Items:

Sl. No.	Item Description	Quantity recommended
1.	Kraft Paper	9.15 kg or applied quantity whichever is less
2.	Base Paper	0.214 kg or applied quantity whichever is less
3.	Barrier Paper	0.172 kg or applied quantity whichever is less
4.	Tissue Paper	0.027 kg or applied quantity whichever is less
5.	Phenol	3.52 kg or applied quantity whichever is less
6.	Melamine	0.362 kg or applied quantity whichever is less
*7.	Paraformaldehyde (91+/-1% Purity)	2.90 kg or applied quantity whichever is less
8.	B.O.P.P. Film	0.01 kg or applied quantity whichever is less

Note:

1. The above norms are based on 10.00 mm thickness with average weight of 14.5 kg +/- 2.5% and are applicable on 1.8 mm and 2.3 mm thickness.
2. In case of variation in thickness/weight, the quantity of item of import viz. Phenol, Methanol and Kraft paper to be allowed may be arrived at by adopting the following formula: $A \times B/C$ where A =Quantity allowed for 10.00 mm thickness of weight.14.5 kg +/- 2.5%, B =The thickness or weight/ sq. Meter of decorative laminates proposed to be exported, C = Either the Standard thickness of 10.00 mm or the Standard weight of 14.5 kg/Sq.Meter of 10.00 mm thickness.
3. The quantity of other items viz. Base Paper, Barrier Paper, Tissue Paper, Melamine and BOPP film will remain unchanged irrespective of thickness and weight of decorative laminate to be exported.
4. Import of Base Paper will be restricted to 18% of FOB value of export, for the export of below 2.5 mm thickness

N22
(NAND LAL)
Consultant
04-07-2019

DGFT (DES-IV)

DGFT file ended

सं. P-47011/154/2019-टीएसडब्ल्यू

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग संवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

155
2/13

213
3/83

विषय :-मैसर्स M/s Samrat Plywood Ltd. का आवेदन इनपुट आउटपुट मानदंडोंके संबंध में । AA No. 2210016075 dated 05.02.2019

संदर्भ:- 01/83/50/00800/AM-19 dated. 19.02.2019

Taking cue from H-68 and the cases approved in the past, the following norms are recommended:-

Export Item:

S. No.	Item Description	Quantity
1	Double Side Decorative Laminates with Barrier Paper size Thickness 2.3 mm (2730 SQM) (9000KG)	750 Number

Import Items:

Sl. No.	Item Description	Quantity recommended
1.	Kraft Paper	9.15 kg or applied quantity whichever is less
2.	Base Paper	0.214 kg or applied quantity whichever is less
3.	Barrier Paper	0.172 kg or applied quantity whichever is less
4.	Tissue Paper	0.027 kg or applied quantity whichever is less
5.	Phenol	3.52 kg or applied quantity whichever is less
6.	Melamine	0.362 kg or applied quantity whichever is less
*7.	Paraformaldehyde (91+/-1% Purity)	2.90 kg or applied quantity whichever is less
8.	B.O.P.P. Film	0.01 kg or applied quantity whichever is less

Note:

1. The above norms are based on 10.00 mm thickness with average weight of 14.5 kg +/- 2.5% and are applicable on 2.3 MM thickness.
2. In case of variation in thickness/weight, the quantity of item of import viz. Phenol, Methanol and Kraft paper to be allowed may be arrived at by adopting the following formula: $A \times B/C$ where A =Quantity allowed for 10.00 mm thickness of weight 14.5 kg +/- 2.5%, B =The thickness or weight/ sq. Meter of decorative laminates proposed to be exported, C = Either the Standard thickness of 10.00 mm or the Standard weight of 14.5 kg/Sq.Meter of 10.00 mm thickness.
3. The quantity of other items viz. Base Paper, Barrier Paper, Tissue Paper, Melamine and BOPP film will remain unchanged irrespective of thickness and weight of decorative laminate to be exported.
4. Import of Base Paper will be restricted to 18% of FOB value of export, for the export of below 2.5 mm thickness

 (NAND LAL)
Consultant
04-07-2019

DGFT (DES-IV)

DGFT file enclosed.

सं . P-47011/163/2019- टीएसडब्लू

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग संवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

Subject: Application of M/s Aica Laminates India Pvt. Ltd. for ratification of input output norms for export of Double Side Decorative Laminates.

Ref: DGFT U.O. No. 01/83/50/01407/AM-19 dated 20.03.2019

Ad. Auth. No. 0510409959 Dated- 15.03.2019

Taking cue from H-68 and the cases approved in the past, the following norms are recommended:-

Export Item:

S. No.	Item Description	Quantity
1	Double Side Decorative Laminates with Barrier Paper Thickness (1.80mm sheet size 2.44Mx1.22M) (as per the application)	35721.60 sq.m

Import Items:

Sl. No.	Item Description	Quantity recommended
1.	Kraft Paper	9.15 kg or applied quantity whichever is less
2.	Base Paper	0.214 kg or applied quantity whichever is less
3.	Barrier Paper	0.172 kg or applied quantity whichever is less
4.	Tissue Paper	0.027 kg or applied quantity whichever is less
5.	Phenol	3.52 kg or applied quantity whichever is less
6.	Melamine	0.362 kg or applied quantity whichever is less
7.	Methanol	3.85 kg or applied quantity whichever is less
8.	B.O.P.P. Film	0.01 kg or applied quantity whichever is less

Note:

1. The above norms are based on 10.00 mm thickness with average weight of 14.5 kg +/- 2.5% and are applicable on 1.80 mm thickness.
2. In case of variation in thickness/weight, the quantity of item of import viz. Phenol, Methanol and Kraft paper to be allowed may be arrived at by adopting the following formula: $A \times B/C$ where A =Quantity allowed for 10.00 mm thickness of weight 14.5 kg +/- 2.5%, B =The thickness or weight/ sq. Meter of decorative laminates proposed to be exported, C = Either the Standard thickness of 10.00 mm or the Standard weight of 14.5 kg/Sq. Meter of 10.00 mm thickness.
3. The quantity of other items viz. Base Paper, Barrier Paper, Tissue Paper, Melamine and BOPP film will remain unchanged irrespective of thickness and weight of decorative laminate to be exported.
4. Import of Base Paper will be restricted to 18% of FOB value of export, for the export of below 2.5 mm thickness.

(Nand Lal)
Consultant
04.07.2019

DGFT(DES-IV)

DGFT file enclosed

Case No 567/235
Impdt 10/7/2019
सं. P-47011/162/2019-टीएसडब्लू
भारत सरकार
वाणिज्य और उद्योग मंत्रालय
उद्योग सवर्धन और आंतरिक व्यापार विभाग
(टीएस अनुभाग)

23/5/19
3/8/19

विषय:- मैसर्स M/s Pacific Industries Ltd. का आवेदन इनपुट आउटपुट मानदंडोंके संबंध में ।
(अग्रिम प्राधिकार सं. 1310049247 दिनांक 29.03.2019)
संदर्भ: 01/83/050/00004/AM 20 Dated: 02.04.2019

In this case the firm will export polished engineered quartz slab and import consumable items for processing/ polishing the quartz slab. The hardness of polished engineered quartz slab is more or less similar to granite stone. Taking cue from SION A1051, A1052 and K133 the following norms are recommended:

Export Item :- Polished Engineered Quartz Slab

Quantity:- 257177.00 sq mtr.

Import Items

S.No	Item Name	Recommendation value wise
1.	Diamond tool for calibrating machine and polishing machine	2.5% of FOB value of export
2.	Polishing Diamond Abrasive	2.5% of FOB value of export

NLE
(Nand Lal)
Consultant
22.07.2019

NC-IV

Encl. D&PT. file ,

सं. P-47011/164/2019-टीएसडब्लू

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग संवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

विषय:- मैसर्स Banaras Beads Ltd. का आवेदन इनपुट आउटपुट मानदंडों के संबंध में

Advance Authorisation No- 1510022181 Dated 18.04.2019

संदर्भ:- 01/83/050/00038/AM 20 Dated: 22.04.2019

In the past norms for the export of similar item using similar import item were approved by DGFT, based on personnel hearing of the firms representative. Taking consideration of the above and information provided in the present application, the following norms are recommended:

Export Item No. 1:- GLASS BEADS & ARTICLE M/O GLASS TUBE SOLID

Quantity:- 25000.00 kg

Import Items

S. No	Item Description	Quantity recommended
1.	Glass Tube Solid	1.50kg/kg content in the export item.
4.	Bead Sticking Powder	2000 kg
5.	Oxalic Acid	2000 kg

Export Item No. 2:- GLASS BEADS M/O GLASS ROD SOLID

Quantity:- 5000.000 kg

Import Item:-

S. No	Item Description	Quantity recommended
2.	Glass Rod Solid	1.20kg/kg content in the export item.

Export Item No. 3:- GLASS BEADS AND ARTICLE THEIR OF M/O GLASS BEADS SOLID

Quantity:- 7500.000 K.G

Import Items:-

S. No	Item Description	Quantity recommended
3.	Glass Beads Solid	1.10kg/kg content in the export item.
6.	Metal Bead And Finding Solid	Net + 5%

DGFT (DES-IV)

(Nand Lal)
Consultant

सं. P-47011/154/2019-टीएसडब्ल्यू

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग संवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

595
21/11/239
3/83

विषय :-मैसर्स M/s Samrat Plywood Ltd. का आवेदन इनपुट आउटपुट मानदंडों के संबंध में । AA No. 2210016132 dated 18.04.2019

संदर्भ:- 01/83/50/00034/AM-20 dated. 22.04.2019

Taking cue from H-68 and the cases approved in the past, the following norms are recommended:-

Export Item:

S. No.	Item Description	Quantity
1	Double Side Decorative Laminates with Barrier Paper size Thickness 1.3 mm (22714 SQM) (43056 KG)	6240 Number
2	Double Side Decorative Laminates with Barrier Paper Thickness 2.2 MM (9027.2 SQM) (26288 KG))	2480 Number

Import Items:

Sl. No.	Item Description	Quantity recommended
1.	Kraft Paper	9.15 kg or applied quantity whichever is less
2.	Base Paper	0.214 kg or applied quantity whichever is less
3.	Barrier Paper	0.172 kg or applied quantity whichever is less
4.	Tissue Paper	0.027 kg or applied quantity whichever is less
5.	Phenol	3.52 kg or applied quantity whichever is less
6.	Melamine	0.362 kg or applied quantity whichever is less
*7.	Paraformaldehyde (91+/-1% Purity)	2.90 kg or applied quantity whichever is less
8.	B.O.P.P. Film	0.01 kg or applied quantity whichever is less

Note:

1. The above norms are based on 10.00 mm thickness with average weight of 14.5 kg +/- 2.5% and are applicable on 1.3 mm and 2.2 mm thickness.
2. In case of variation in thickness/weight, the quantity of item of import viz. Phenol, Methanol and Kraft paper to be allowed may be arrived at by adopting the following formula: $A \times B/C$ where A =Quantity allowed for 10.00 mm thickness of weight 14.5 kg +/- 2.5%, B =The thickness or weight/ sq. Meter of decorative laminates proposed to be exported, C = Either the Standard thickness of 10.00 mm or the Standard weight of 14.5 kg/Sq.Meter of 10.00 mm thickness.
3. The quantity of other items viz. Base Paper, Barrier Paper, Tissue Paper, Melamine and BOPP film will remain unchanged irrespective of thickness and weight of decorative laminate to be exported.
4. Import of Base Paper will be restricted to 18% of FOB value of export, for the export of below 2.5 mm thickness


(NAND LAL)
Consultant
04-07-2019

DGFT (DES-IV)

DGFT के एवम

सं. P-47011/173/2019-टीएसडब्लू

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग संवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

24/5
13/83

विषय:- मैसर्स Polyon Textiles Pvt Ltd का आवेदन इनपुट आउटपुट मानदंडों के संबंध में।

संदर्भ: 01/83/050/00081/AM 20/ Dated: 15.05.2019

(Adv License - 08/01/452/19 dt 15/05/2019)

In this case the firm has claimed 15% wastage for glass fiber roving and 11% for non woven geo textile for the manufacture of Fiber Glass Reinforced Grid. Besides above items they will use Bitumen Copolymer and Acralate Copolymer for making export product. Taking cue from SION A 1037, wastage of 5% may be allowed for Glass Fiber Roving and Non Woven Geo Textile. Accordingly, following norms are recommended.

Export Item:- Fiber Glass Reinforced Grid

Quantity:- 63000 Kg

Import Items

S. No.	Import Item Name	Quantity
1.	Glass Fiber Rovings	1.05 kg/ kg content in the export product
2.	Non Woven Geo Textiles	1.05 kg/ kg content in the export product

NL

(Nand Lal)

Consultant

26.07.2019

DGFT (DES-IV)

F. No. 7/80/2019-TSW

भारत सरकार

वाणिज्य और उद्योग मंत्रालय

उद्योग सवर्धन और आंतरिक व्यापार विभाग

(टीएस अनुभाग)

267110
3/83

Sub:- AA Nos. 0510407426 dated 03.08.2018, 0510406825 dated 12.06.2018, 0510410576 dated 14.05.2019 & 0510407962 dated 03.10.2018 for the export of engineered wooden flooring- M/s. Green Lam Industries Ltd.

Ref: - I) 01/83/050/00490/AM19/DES-IV
ii) 01/83/050/00981/AM19/DES-IV
iii) 01/83/050/00114/AM20/DES-IV
iv) 01/83/050/00618/ AM19/DES-IV

In this case export produced product is "Engineered wooden flooring " (15.00 m) and import items are

S. No.	Import item	Wastage claimed
1.	Wood Veneer (for Top Layer)	66.67%
2.	Pine wood (for Middle Layer)	100%
3.	Wood Veneer (for Bottom layer)	53.85%
4.-8.	Glue, modifier, hardener and lacquer/paint/varnish	20%

The firm was called for personal hearing by DGFT and the firm's representatives explained the manufacturing process and wastage occurring in manufacturing the export product, giving calculation for requirement of raw materials. It has been stated that the wooden flooring has plank lock which is used to join wooden flooring with each other on the floor. There are three layers of wooden flooring and import items are 1 to 3 as stated above. The wastage is due to following reason:

- Grading Wastage because this is a natural material having some kind of holes, knots, sap wood, water mark, cracks, because of these the material becomes unusable.
- The Raw Material comes in different sizes and grades. However, the finished product requires fixed sizes and premium grade only.
- The material is required to store at a certain degree of moisture therefore, the material is stored in seasoning chamber, and thus the shrinkage wastage is also very higher.

d. Cutting wastage is also there.

After deliberation, Committee decided to fix the following norms, on one time basis in all the four A.As. as under:

Export Items: Engineered Wooden Flooring (thickness: 15.00MM)
Quantity: 1 Sq Meter

Import Items;

S.No	Item Description	Quantity recommended
1.	Wood Veneer (for top layer) (thickness:3.00MM+/- 10%)	1.5670 SQM.
2.	Pine Wood (for middle layer)	0.0188 CBM
3.	Wood Veneer (for bottom layer) (Thickness: 2.20 MM +/-10%)	0.00318 CBM
4.	Glue-urea formaldehyde	0.2338 Kg
5.	Modifier	0.0475 Kg
6.	Hardner	0.0400 Kg
7.	Lacquer/paint (UV sealer standard, UV sealer anti abrasive, UV top coat anti scratch, UV sealer matt, UV primer, UV filler, UV hydro primer white, UV sealer colourless, UV sealer lifetime, UV sealer white, UV top coat entry scratch matt, stain binder)	0.1365 Kg
8.	Lacquer/ Varnish (colour yellow, red, white, black, blue)	0.0080 Kg

DES-IV

NLP
24/7/2019
(Nand Lal)
Consultant